



ARGUS **ADVANTA**[®]

ER-700

ECONOMY RADIAL TIRES

Superior Traction:

- Symmetrical tread design provides increased dry, wet and light snow traction.

Solid Center Rib:

- Improves on-line steering feel, stability and tread wear.

High-Speed Maneuverability:

- High angle tread blocks designed to extend the contact patch combined with symmetrical tread design enhance high speed cornering and stability.
- 45,000-mile limited treadwear warranty.



ER-700



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
ER700215	225/60R17	99	T	STD	460AB	10	BLK	6.0-8.0	8.98	27.64	1709	26.4
ER700105	175/65R14	82	H	STD	420AA	10	BLK	5.0-6.0	6.97	22.99	1047	15.2
ER700100	185/60R14	82	H	STD	420AA	10	BLK	5.0-6.5	7.44	22.76	1047	15.7
ER700125	185/60R15	84	H	STD	420AA	10	BLK	5.0-6.5	7.44	23.74	1102	17.2
ER700110	185/65R14	82	H	STD	420AA	10	BLK	5.0-6.5	7.44	23.46	1047	16.1
ER700135	185/65R15	88	H	STD	420AA	10	BLK	5.0-6.5	7.44	24.45	1235	17.0
ER700115	185/70R14	88	T	STD	460AB	10	BLK	4.5-6.0	7.44	24.25	1235	17.2
ER700130	195/60R15	88	H	STD	420AA	10	BLK	5.5-7.0	7.91	24.21	1235	18.3
ER700140	195/65R15	91	H	STD	420AA	10	BLK	5.5-7.0	7.91	25.00	1356	19.4
ER700120	195/70R14	91	T	STD	460AB	10	BLK	5.0-6.5	7.91	24.80	1356	19.0
ER700160	205/55R16	91	V	STD	420AA	10	BLK	5.5-7.5	8.43	24.88	1356	20.7
ER700170	205/60R16	92	V	STD	420AA	10	BLK	5.5-7.5	8.23	25.67	1389	20.9
ER700145	205/65R15	94	H	STD	420AA	10	BLK	5.5-7.5	8.23	25.47	1477	21.2
ER700165	215/55R16	97	H	XL	420AA	10	BLK	6.0-7.5	8.90	25.28	1609	22.0
ER700200	215/55R17	94	V	STD	420AA	10	BLK	6.0-7.5	8.90	26.30	1477	22.4
ER700175	215/60R16	95	V	STD	420AA	10	BLK	6.0-7.5	8.70	26.14	1521	22.9
ER700210	215/60R17	96	T	STD	460AB	10	BLK	5.5-7.5	8.70	27.17	1565	24.4
ER700185	215/65R16	98	T	STD	420AA	10	BLK	6.0-7.5	8.70	27.01	1653	24.9
ER700220	215/65R17	99	T	STD	460AB	10	BLK	6.0-8.0	8.70	28.04	1709	25.3
ER700195	225/50R17	94	V	STD	420AA	10	BLK	6.0-8.0	9.17	25.91	1477	23.5
ER700205	225/55R17	97	V	STD	420AA	10	BLK	6.0-8.0	9.17	26.78	1609	24.6
ER700180	225/60R16	98	H	STD	420AA	10	BLK	6.0-8.0	8.98	26.61	1653	24.5
ER700225	225/65R17	102	T	STD	460AB	10	BLK	6.0-7.5	8.98	28.51	1874	26.6



ARGUS ADVANTA[®]

HPZ-01

HIGH PERFORMANCE TIRES

- Outstanding Ride Control:
Tread designed for stability with a large contact patch
- Noise treated tread design for an exceptionally quiet ride
- All season design and M&S rated for all driving conditions
- Exceptional wet and dry performance in all weather conditions
- 40,000-mile limited treadwear warranty



ECOSAFE

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range	Overall Width (in.)	Overall Diameter (in.)	Max Load	
											Single/ Dual (lbs.)	Tire Weight (lbs.)
1951357400	205/40ZR17 XL	84	W	XL	420 AA A	10	BLK	7-8	9	23.5	1102	19.8
1951357500	205/50ZR17 XL	93	W	XL	420 AA A	10	BLK	5.5-7.5	9	25.1	1433	22.9
1951357401	215/40ZR17 XL	87	W	XL	420 AA A	10	BLK	7-8.5	9	23.8	1201	21.4
1951357451	215/45ZR17 XL	91	W	XL	420 AA A	10	BLK	7-8	9	24.7	1356	22.5
1951357501	215/50ZR17 XL	95	V	XL	420 AA A	10	BLK	6-7.5	9	25.5	1521	23.7
1951357551	215/55ZR17 XL	98	W	XL	420 AA A	10	BLK	6-7.5	9	26.3	1653	22.5
1951357452	225/45ZR17 XL	94	W	XL	420 AA A	10	BLK	7-8	9	25	1477	23.2
1951357502	225/50ZR17 XL	98	V	XL	420 AA A	10	BLK	6-8	10	25.9	1653	24.3
1951357552	225/55R17 XL	101	V	XL	420 AA A	10	BLK	6-8	10	26.8	1819	25
1951357453	235/45ZR17 XL	97	W	XL	420 AA A	10	BLK	7.5-9	10	25.4	1609	23.8
1951357553	235/55R17 XL	103	V	XL	420 AA A	10	BLK	6.5-8.5	10	27.2	1929	26
1951357404	245/40ZR17 XL	95	W	XL	420 AA A	10	BLK	8-9.5	10	24.7	1521	24.3
1951357454	245/45ZR17 XL	99	W	XL	420 AA A	10	BLK	7.5-9	10	25.7	1709	24.5
1951358351	215/35ZR18 XL	84	W	XL	420 AA A	10	BLK	7-8.5	9	23.9	1102	22.1
1951358401	215/40ZR18 XL	89	W	XL	420 AA A	10	BLK	7-8.5	9	24.8	1279	21.2
1951358402	225/40ZR18 XL	92	W	XL	420 AA A	10	BLK	7.5-9	9	25.1	1389	23.3
1951358452	225/45ZR18 XL	95	W	XL	420 AA A	10	BLK	7-8.5	9	25.9	1521	24.7
1951358403	235/40ZR18 XL	95	W	XL	420 AA A	10	BLK	8-9.5	10	25.4	1521	23.8
1951358503	235/50ZR18 XL	101	W	XL	420 AA A	10	BLK	6.5-8.5	10	27.3	1819	26
1951358553	235/55ZR18 XL	104	W	XL	420 AA A	10	BLK	6.5-8.5	10	28.2	1984	29.1
1951358404	245/40ZR18 XL	97	W	XL	420 AA A	10	BLK	8-9.5	10	25.7	1609	26.4
1951358454	245/45ZR18 XL	100	W	XL	420 AA A	10	BLK	7.5-9	10	26.7	1764	26.2
1951358355	255/35ZR18 XL	94	W	XL	420 AA A	10	BLK	8.5-10	11	25	1477	24.9
1951358455	255/45ZR18 XL	103	W	XL	420 AA A	10	BLK	8-9.5	10	27.1	1930	28.2
1951358555	255/55ZR18 XL	109	W	XL	420 AA A	10	BLK	7-9	10	29	2270	33.1
1951359352	225/35ZR19 XL	88	W	XL	420 AA A	10	BLK	7-8.5	9	25.2	1235	23.9
1951359402	225/40ZR19 XL	93	W	XL	420 AA A	10	BLK	8-9.5	9	26.1	1433	23.7
1951359552	225/55R19 SL	99	H	SL	420 AA A	10	BLK	6-8	10	28.8	1709	27.1
1951359353	235/35ZR19 XL	91	W	XL	420 AA A	10	BLK	7-8.5	9	25.5	1356	23.9
1951359354	245/35ZR19 XL	93	W	XL	420 AA A	10	BLK	8-9.5	10	25.8	1433	24.6
1951359404	245/40ZR19 XL	98	W	XL	420 AA A	10	BLK	8-9.5	10	26.7	1653	25.9
1951359454	245/45ZR19 XL	102	W	XL	420 AA A	10	BLK	7.50-9	10	27.7	1875	27.1
1951359355	255/35ZR19 XL	96	W	XL	420 AA A	10	BLK	8-9.5	11	26	1565	25.5
1951359306	265/30ZR19 XL	93	W	XL	420 AA A	10	BLK		11	25.3	1433	25.3
1951359307	275/30ZR19 XL	96	W	XL	420 AA A	10	BLK	9-10	11	25.6	1565	26.1
1951350302	225/30ZR20 XL	85	W	XL	420 AA A	10	BLK	7.5-9	9	25.4	1135	21.9
1951350352	225/35ZR20 XL	90	W	XL	420 AA A	10	BLK	7.5-9	9	26.2	1323	21.9
1951350304	245/30ZR20 XL	90	W	XL	420 AA A	10	BLK		10	25.8	1323	24.7
1951350354	245/35ZR20 XL	95	W	XL	420 AA A	10	BLK	8.5-10	10	26.8	1521	25.7
1951350404	245/40ZR20 XL	99	W	XL	420 AA A	10	BLK	8-9.5	10	27.7	1709	27.1
1951350454	245/45ZR20 SL	99	W	SL	420 AA A	10	BLK	8-9.5	10	28.7	1709	28
1951350355	255/35ZR20 XL	97	W	XL	420 AA A	10	BLK	8.5-10	11	27	1609	26.4
1951350455	255/45ZR20 XL	105	W	XL	420 AA A	10	BLK	8-9.5	10	29.1	2039	29.4
1951350307	275/30ZR20 XL	97	W	XL	420 AA A	10	BLK	9-10	11	26.5	1609	27.4
1951352407	275/40ZR20 XL	106	W	XL	420 AA A	10	BLK	9-11	11	28.7	2094	30.9
1951350457	275/45R20 XL	110	V	XL	420 AA A	10	BLK	8.5-10.5	11	29.8	2337	32.2
1951350557	275/55R20 XL	117	V	XL	420 AA A	10	BLK	7.5-9.5	12	31.9	2833	36.6
1951350258	285/25ZR20 XL	93	W	XL	420 AA A	10	BLK		12	25.6	1433	28.6
1951352303	235/30ZR22 XL	90	W	XL	420 AA A	10	BLK		10	27.6	1323	21.9
1951352304	245/30ZR22 XL	92	W	XL	420 AA A	10	BLK		10	27.8	1389	26.5
1951352305	255/30ZR22 XL	95	W	XL	420 AA A	10	BLK		11	28.1	1521	25.6
1951352306	265/30ZR22 XL	97	W	XL	420 AA A	10	BLK		11	28.3	1609	29.3
1951352355	265/35ZR22 XL	102	W	XL	420 AA A	10	BLK	9.5-10.5	11	29.3	1874	30.3
1951352258	285/25ZR22 XL	95	W	XL	420 AA A	10	BLK		12	27.6	1521	30.2
1951352458	285/45ZR22 XL	114	W	XL	420 AA A	10	BLK	9-10.5	12	32.1	2601	35.3
1951352259	295/25ZR22 XL	97	W	XL	420 AA A	10	BLK		12	27.8	1609	31.8
1951352400	305/40ZR22 XL	114	W	XL	420 AA A	10	BLK	10-12	13	31.6	2601	40.1
1951352450	305/45R22 XL	118	V	XL	420 AA A	10	BLK	9.5-11.5	12	32.8	2910	40.4
1951354305	255/30ZR24 XL	97	W	XL	420 AA A	10	BLK	8.5-9.5	11	30.1	1609	30.4
1951354257	275/25ZR24 XL	96	W	XL	420 AA A	10	BLK	9.5-10.5	11	29.5	1565	30.9
1951354450	305/35R24 XL	112	V	XL	420 AA A	10	BLK	10-12	13	32.4	2469	41
1951356257	275/25ZR26 XL	98	W	XL	420 AA A	10	BLK	9.5-10.5	11	31.4	1653	34.1
1951356309	295/30ZR26 XL	107	W	XL	420 AA A	10	BLK		12	33	2149	38.3
1951356300	305/30R26 XL	109	V	XL	420 AA A	10	BLK		13	33.2	2271	41.6



ARGUS ADVANTA[®]

HTR-700

LIGHT TRUCK HIGHWAY TERRAIN

- LT rated 10 ply tires designed for carrying heavy cargo and towing large trailers.
- Wide 5-rib highway tread offers combination of superb handling and braking on wet and dry surfaces.
- Designed for a quiet, comfortable ride and maximum performance for highway applications in all weather conditions.
- Strong steel belted construction ensures exceptional stability, durability and long tread life.
- M & S Rated



ECOSAFE

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



HTR-700



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	Ply Rating	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
1932401863	LT215/85R16	115/112	Q	E	10	15	BLK	5.5 - 7.0	8.5	30.4	2680/2470	37.0
1932402763	LT225/75R16	115/112	Q	E	10	15	BLK	6.0 - 8.0	8.8	29.3	2680/2470	38.6
1932403863	LT235/85R16	120/116	Q	E	10	15	BLK	6.0 - 7.5	9.3	31.7	3042/2778	42.7
1932404763	LT245/75R16	120/116	Q	E	10	15	BLK	6.5 - 8.0	9.8	30.5	3042/2778	43.3
1932406763	LT265/75R16	123/120	Q	E	10	15	BLK	7.0 - 8.0	10.5	31.7	3415/3085	47.6
1932404773	LT245/75R17	121/118	Q	E	10	15	BLK	6.5 - 7.5	9.8	31.5	3195/2910	43.2
1932407763	LT265/70R17	121/118	Q	E	10	15	BLK	7.0 - 8.5	10.7	31.7	3195/2910	47.4



ARGUS ADVANTA[®]

SVT-01

RADIAL SUV TIRES

- Designed for maximum performance for all sport utility vehicle applications.
- Tread design is noise treated to ensure smooth, quiet ride on all road surfaces.
- Designed for exceptional handling, braking and acceleration.
- Sturdy steel belt construction to ensure stability, durability and long tread life.
- M & S Rated
- 60,000-mile limited treadwear warranty.



ECOSAFE

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



SVT-01



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
1932436715	P215/70R16	99	T	SL	520 A A	11	BLK	5.5 - 7.0	8.7	27.9	1709	27.6
1932436735	P235/70R16	104	T	SL	520 A A	11	BLK	6.0 - 8.0	9.5	29.0	1984	30.7
1932437615	P215/60R17	95	V	SL	520 A A	11	BLK	6.0 - 7.5	8.7	27.2	1521	27.6
1932437625	P225/65R17	100	T	SL	520 A A	11	BLK	6.5 - 8.0	9.0	28.5	1764	29.1
1932437635	P235/65R17	103	T	SL	520 A A	11	BLK	6.5 - 8.0	9.5	29.1	1929	30.9
1932437645	P245/65R17	105	T	SL	520 A A	11	BLK	7.0 - 8.5	9.8	29.5	2039	32.3
1932437745	P245/70R17	108	T	SL	520 A A	11	BLK	6.5 - 8.0	9.8	30.6	2205	33.7
1932437665	P265/65R17	110	T	SL	520 A A	11	BLK	7.5 - 9.5	10.7	30.6	2337	35.8
1932437765	P265/70R17	113	T	SL	520 A A	11	BLK	7.0 - 9.0	10.7	31.7	2535	37.3
1932438255	P225/55R18	97	H	SL	520 A A	11	BLK	6.0 - 8.0	9.2	27.8	1609	28.4
1932438635	P235/60R18	102	T	SL	520 A A	11	BLK	6.5 - 8.5	9.5	29.1	1874	31.6
1932438355	P235/65R18	104	H	SL	520 A A	11	BLK	6.5 - 8.5	9.5	30.0	1984	32.7
1932438645	P245/60R18	104	T	SL	520 A A	11	BLK	7.0 - 8.5	9.8	29.6	1984	32.6
1932438555	P255/65R18	109	H	SL	520 A A	11	BLK	7.0 - 9.0	10.2	31.1	2271	34.5
1932438765	P265/70R18	114	T	SL	520 A A	11	BLK	7.0 - 9.0	10.7	32.6	2601	39.0
1932438755	P275/65R18	114	H	SL	520 A A	11	BLK	7.5 - 9.5	11.0	32.1	2601	39.8
1932439355	P235/55R19XL	105	V	XL	520 A A	11	BLK	6.5 - 8.5	9.7	29.2	2039	31.6
1932439455	P245/55R19	103	H	SL	520 A A	11	BLK	7.0 - 8.5	10.0	29.7	1929	33.0
1932432575	P275/55R20	117	T	SL	520 A A	11	BLK	7.5 - 9.5	11.2	31.9	2833	43.0
1932432675	P275/60R20	115	T	SL	520 A A	11	BLK	7.5 - 9.5	11.0	33.0	2679	46.0



ARGUS ADVANTA[®]

TRG-750

PASSENGER TOURING TIRES

- Fits Broadline sedans, coupes, compacts and vans with speed rated sizing for today's popular vehicle fitments
- Technology-driven tread design for superior all-weather performance
- Precision engineered for even wear and long tread life
- Full-depth siping for long lasting wet and snow traction
- Notched center rib with multi-element blading for improved handling and steering response
- 60,000 mile treadwear warranty T rated
- 50,000 mile treadwear warranty H/V rated

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



TRG-750



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
TRG750100	185/65R14	86	T	STD	500AB	10	SBL	5.0-6.5	7.44	23.46	1168	16.8
TRG750105	185/60R15	84	T	STD	500AB	10	SBL	5.0-6.5	7.44	23.74	1102	18.5
TRG750110	195/60R15	88	H	STD	460AA	10	SBL	5.5-7.0	7.91	24.21	1235	18.4
TRG750115	185/65R15	88	T	STD	500AB	10	SBL	5.0-6.5	7.44	24.45	1235	17.6
TRG750120	195/65R15	91	T	STD	500AB	10	SBL	5.5-7.0	7.91	25.00	1356	20.3
TRG750125	205/65R15	94	T	STD	500AB	10	SBL	5.5-7.5	8.23	26.46	1477	21.7
TRG750130	215/65R16	98	T	STD	500AB	10	SBL	6.0-7.5	8.23	25.47	1653	25.0
TRG750135	205/70R15	96	T	STD	500AB	10	SBL	5.0-7.0	8.70	26.89	1565	23.7
TRG750140	215/70R15	98	T	STD	500AB	10	SBL	5.5-7.0	8.23	26.34	1653	25.2
TRG750145	205/55R16	91	H	STD	460AA	10	SBL	5.5-7.5	8.43	24.88	1356	21.3
TRG750150	215/55R16	97	H	STD	460AA	10	SBL	6.0-7.5	8.90	25.28	1609	23.4
TRG750155	205/60R16	92	H	STD	460AA	10	SBL	5.5-7.5	8.70	25.16	1389	21.6
TRG750160	215/60R16	95	T	STD	500AB	10	SBL	6.0-7.5	8.70	26.14	1521	24.3
TRG750165	225/60R16	98	T	STD	500AB	10	SBL	6.0-8.0	8.70	27.17	1653	25.4
TRG750175	205/65R16	95	H	STD	460AA	10	SBL	5.5-7.5	8.70	27.01	1521	21.5
TRG750180	225/65R16	100	T	STD	500AB	10	SBL	6.0-8.0	8.98	27.48	1764	25.9
TRG750185	235/65R16	103	T	STD	500AB	10	SBL	6.5-8.5	9.45	28.03	1929	26.7
TRG750190	205/50R17	89	V	STD	380AA	10	SBL	5.5-7.5	8.43	25.12	1279	21.3
TRG750200	225/50R17	94	V	STD	380AA	10	SBL	6.0-8.0	9.17	25.91	1477	25.4
TRG750205	215/55R17	94	V	STD	380AA	10	SBL	6.0-7.5	8.90	26.30	1477	24.6
TRG750210	225/55R17	97	T	STD	500AB	10	SBL	6.0-8.0	9.17	26.77	1609	25.8
TRG750215	215/60R17	96	T	STD	500AB	10	SBL	6.0-7.5	8.98	27.64	1565	25.3
TRG750220	225/60R17	99	T	STD	500AB	10	SBL	6.0-8.0	8.98	26.61	1709	26.4
TRG750225	225/65R17	102	T	STD	500AB	10	SBL	6.0-8.0	8.98	28.50	1653	30.0



ARGUS **ADVANTA**®

ATX-750

ALL TERRAIN LIGHT TRUCK TIRES

- 3 Peak Mountain Snowflake Certified (3PMS) for severe snow performance.
- Aggressive open shoulder design increases stability and traction in all weather conditions.
- Stone ejectors withstand harsh road conditions.
- Trapezoidal claw design on the shoulder edge increases traction in snow and mud, dissipates heat and enhances durability.
- Jagged edge tread blocks improve grip on ice and in the mud providing superior traction.
- Zig zag grooves and continuous center block provide outstanding grip and superior handling.
- 50,000 mile limited treadwear warranty P metric rated
- 50,000 mile limited treadwear warranty LT rated.

ARGUS ADVANTA is a registered trademark of American Pacific Industries, Inc.



ATX-750



Part Number	Tire Size	Load Index	Speed Symbol	Load Range	UTQG	Tread Depth 32nds	Side-wall	Rim Width Range (in.)	Overall Width (in.)	Overall Diameter (in.)	Max Load Single/Dual (lbs.)	Tire Weight (lbs.)
ATX750100	235/75R15	109	S	SL	500AB	13	OWL	6.0-8.0	9.25	28.86	2271	31.5
ATX750105	235/70R16	106	S	SL	500AB	13	OWL	6.0-8.0	9.45	28.98	2094	31.2
ATX750110	245/75R16	111	S	SL	500AB	13	OWL	6.5-8.0	9.76	30.47	2403	35.2
ATX750115	265/75R16	116	S	SL	500AB	13	OWL	7.0-9.0	10.51	31.65	2756	38.1
ATX750120	265/70R16	112	T	SL	500AB	13	OWL	7.0-9.0	10.71	30.63	2469	37.1
ATX750125	245/65R17	107	S	SL	500AB	13	OWL	7.0-8.5	9.76	29.53	2149	33.3
ATX750130	265/65R17	112	S	SL	500AB	13	OWL	7.5-9.5	10.71	30.55	2469	37.2
ATX750135	265/70R17	115	S	SL	500AB	13	OWL	7.0-9.0	10.71	31.65	2679	39.0
ATX750140	275/65R18	116	T	SL	500AB	13	OWL	7.5-9.5	10.98	32.09	2756	39.9
ATX750145	275/60R20	115	T	SL	500AB	13	BSW	7.5-9.5	10.98	32.99	2679	40.8
ATX750150	275/55R20	117	T	XL	500AB	13	BSW	7.5-9.5	11.18	31.89	2833	40.1
ATX750155	LT225/75R16	115/112	S	10/E	-	16	BSW	6.0-7.0	8.78	29.29	2680/2470	36.6
ATX750160	LT285/75R16	126/123	R	10/E	-	16	OWL	7.5-9.5	11.26	32.83	3750/3415	49.3
ATX750165	LT245/75R16	120/116	S	10/E	-	16	BSW	6.5-8.0	9.76	30.47	3042/2778	41.3
ATX750170	LT265/75R16	123/120	S	10/E	-	16	OWL	7.0-8.0	10.51	31.65	3415/3085	45.2
ATX750175	LT235/85R16	120/116	R	10/E	-	16	BSW	6.0-7.5	9.25	31.73	3042/2778	41.7
ATX750180	LT235/80R17	120/117	R	10/E	-	16	OWL	6.0-7.5	9.25	31.81	3085/2835	41.5
ATX750185	LT245/70R17	119/116	S	10/E	-	16	OWL	6.5-8.0	9.76	30.55	3000/2755	41.6
ATX750190	LT245/75R17	121/118	S	10/E	-	16	OWL	6.5-7.5	9.76	31.50	3195/2910	42.9
ATX750195	LT265/70R17	121/118	S	10/E	-	16	OWL	7.0-8.5	10.71	31.65	3195/2910	45.6
ATX750200	LT285/70R17	121/118	R	10/E	-	16	OWL	7.5-9.0	11.50	32.76	3195/2910	49.6
ATX750205	LT265/70R18	124/121	R	10/E	-	16	BSW	7.0-9.0	10.71	32.64	3525/3195	47.0
ATX750210	LT275/70R18	125/122	R	10/E	-	16	OWL	7.0-8.5	10.98	33.19	3640/3305	49.4
ATX750215	LT275/65R18	123/120	R	10/E	-	16	OWL	7.5-9.0	10.98	32.09	3415/3085	47.5
ATX750220	LT275/65R20	126/123	R	10/E	-	16	BSW	7.5-9.5	10.98	34.09	3750/3415	50.7
ATX750225	31x10.50R15LT	109	S	6/C	-	16	OWL	7.0-9.0	10.54	30.52	2270	40.0